

WAKOL PK 4540 Colour Paste, grey

Technical Information

Area of application

Grey colour paste to stain all kind of not dark coloured Wakol MS-parquet adhesives, Wakol polyurethane adhesives and Wakol dispersion adhesives.

Special properties

- product features of the parquet adhesives stay preserved
- solvent-free*
- no stress whitening in combination with Wakol MS-parquet adhesives

* solvent-free according to the definition of the TRGS 610

Technical data

| | |
|---------------------|---|
| Raw material base: | pigment concentrate |
| Max. Dosage amount: | 1 tube per packaging polyurethane parquet adhesive; 2 tubes per packaging Wakol MS parquet adhesive and Wakol dispersion adhesive |
| Storage time: | 24 months at 20°C |
| GISCODE: | non-applicable |

Usage

Make a cut at the bottom of the inliner of Wakol MS-parquet adhesives and pour the adhesive into the bucket.

Add WAKOL PK 4540 Colour paste, grey to the corresponding adhesive. The addition can take place at the same time with the hardener of 2-K polyurethane adhesives.

Stir in intensely the WAKOL PK 4540 Colour paste, grey for at least 3 minutes and afterwards process the adhesive as usual.

Observe the Technical Information Sheet of the parquet flooring manufactures as well.

Important

Lower addition amounts results in brighter grey tones. The adhesive can be individually adapt at the colour of the parquet, but do not exceed the maximum dosage.

The colour of the dispersion adhesive, after the stirring of the colour paste, is brighter in fresh condition. After the drying, the colour gets darker.

On top opened adhesive joints getting brighter after sanding. After using of finishing materials, adhesive gets darker again.

WAKOL PK 4540 Colour paste, grey is not suitable for dyeing synthetic resin solvents.

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the currently applicable codes must be observed. We gladly provide technical advice.

The product data sheets can be found in their latest version at www.wakol.com.

This Technical Information of 10.07.2012 supersedes all previous versions.