

WAKOL D 3319 PVC Design Flooring Adhesive, contains fibre

Technical information

Area of application

Fibre-reinforced dispersion-based wet adhesive according to DIN EN 14259 for the laying of

- CVT design floorings in planks and tiles
- Homogeneous and heterogeneous PVC floorings in planks and tiles
- CV floorings

on absorbent subfloors indoors.

Special properties



1)



2)

- solvent-free according to TRGS 610
- complies with DIN EN 14259
- optimised indentation
- suitable for underfloor heating
- suitable for chair castors

1) Based on the criteria of GEV (Association for Emission-Controlled Laying Materials), classified as EMICODE EC1 PLUS: very low in emissions

2) Emission class according to French law

Technical data

Raw material basis:	Acrylate dispersion
Airing time:	approx. 5 - 10 minutes
Open time:	approx. 10 - 20 minutes
Cleaning agent:	Water, before the adhesive starts to dry
Storage time:	12 months at room temperature
Storage temperature:	not below +5 °C; sensitive to frost
GISCODE:	D1
EMICODE according to GEV:	EC1 PLUS

Application method and consumption³⁾:

TKB A2 approx. PVC and CV floorings
250 - 300 g/m²

3) Consumption depends on the surface structure and absorbability of the subfloor

Subfloors

The subfloor and the climatic conditions of the room must meet the requirements of DIN 18365. Subfloors must be level, permanently dry, solid and free from cracks, dirt and adhesion-inhibiting substances.

Apply corresponding Wakol levelling compounds to non-absorbent and uneven subfloors. The technical information on the primers and levelling compounds must be heeded.

Usage

Stir adhesive well before using. Using a notched trowel, apply uniformly on the subfloor, avoiding adhesive pools. Lay flooring after appropriate airing time and rub well. Rub down a short time later.

Important

Do not use at temperatures below +15 °C. In cold weather, warm up WAKOL D 3319 PVC Design Flooring Adhesive, contains fibre in due time in heated room. All information is based on approx. 20 °C and 65 % relative air humidity.

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the currently applicable codes must be observed. We gladly provide technical advice.

The product data sheets can be found in their latest version at www.wakol.com.

This Technical Information of 09.07.2015 supersedes all previous versions.