

WAKOL S 28 Sprinkling Sand

Technical information

Area of application

Washed and annealed sand with irregular grain and a grain size of 0.2 - 0.8 mm for sprinkling reaction primers and reaction adhesives as well as WAKOL PS 205 Cast Resin.

Technical data

Raw material base:	broken special-sand
Grain size:	0.2 - 0.8 mm
Coverage:	approx. 500 - 1000 g/m ² , depending on surface evenness of the subfloor
Storage:	store dry, not susceptible of freezing
Storage time:	unlimited in the sealed containers

Method of use

Sprinkle WAKOL S 28 Sprinkling Sand in the fresh synthetic resin primer or adhesive. Sprinkle enough sand so that it is not "submerged" in the primer and there remains a surface that is completely sandy.

After the primer or adhesive has fully hardened, remove excess sand that is not firmly bonded by using a hard broom. Before proceeding further vacuum surface with appropriate industrial vacuum cleaner.

Important

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the currently applicable codes must be observed. We gladly provide technical advice.

The product data sheets can be found in their latest version at www.wakol.com.

This Technical Information of 10.07.2012 supersedes all previous versions.

Wakol GmbH
Bottenbacher Straße 30
D-66954
Pirmasens
Tel. +49 6331 8001 131
Fax +49 6331 8001 890
www.wakol.com



Wakol GmbH
Industriestraße 5
A-6841
Mäder
Tel. +43 5523 64 700
Fax +43 5523 64 700 64
www.wakol.at

Wakol Adhesa AG/SA
Stauffacherstraße 130 A
CH-3014
Bern
Tel. +41 31 9210 755
Fax +41 31 9212 968
www.wakoladhesa.ch

Wakol Foreco srl
Via Kennedy 75
I-20010
Marcallo con Casone
Tel. +39 02 9761 939
Fax +39 02 97 253 021
www.wakolforeco.it

Loba-Wakol Polska Sp. z o.o.
ul. Sławęcinska 16, Macierzysz
PL-05-850
Ożarów Mazowiecki
Tel. +48 22 436 24 20
Fax +48 22 436 24 21
www.loba-wakol.pl

Maiburg Lijmen B.V.
Schutweg 6
NL-5145 NP
Waalwijk
Tel. +31 416 566 530
Fax +31 416 566 531
www.maiburg.nl